

Claims

What is claimed is:

- 5 1. A digital signaling system comprising:
a transmit circuit, the transmit circuit comprising a transmit data input and a
transmit data output, the transmit circuit producing an transmit data output signal at the
transmit data output based on a transmit data input signal from the transmit data input
when the transmit circuit is operating in a normal mode, the transmit circuit further
10 comprising a transmit repeating pattern generator producing a repeating pattern signal,
the transmit circuit producing the transmit data output signal at the transmit data output
based on the repeating pattern signal when the transmit circuit is operating in a test mode;
and
a receive circuit, the receive circuit operably coupled to the transmit circuit and
15 receiving the transmit data output signal from the transmit circuit at a receive data input,
the receive circuit comprising a receive data output, the receive circuit producing a
receive data output signal at the receive data output based on transmit data output signal
when the receive circuit is operating in the normal mode, the receive circuit further
comprising a receive repeating pattern generator producing the repeating pattern signal,
20 the receive circuit producing a comparison signal based on comparison dependent on the
transmit data output signal and the repeating pattern signal when the receive circuit is
operating in the test mode.
2. The digital signaling system of claim 1 wherein the transmit repeating pattern
25 generator comprises a transmit shift register and the receive repeating pattern generator
comprises a receive shift register.
3. The digital signaling system of claim 2 wherein a transmit shift register output of
the transmit shift register is coupled a transmit shift register input of the transmit shift
30 register when the transmit circuit is operating in the test mode and a receive shift register

output of the receive shift register is coupled to a receive shift register input of the receive shift register when the receive circuit is operating in the test mode.

4. The digital signaling system of claim 2 wherein the transmit circuit further
5 comprises a transmit linear feedback logic gate, wherein a first transmit shift register
output of the transmit shift register is coupled a first transmit linear feedback logic input
of the transmit linear feedback logic gate and wherein a second transmit shift register
output of the transmit shift register is coupled a second transmit linear feedback logic
input of the transmit linear feedback logic gate, the transmit linear feedback logic gate
10 producing a transmit linear feedback logic gate output signal upon which a transmit shift
register input signal at a transmit shift register input of the transmit shift register depends
when the transmit circuit is operating in the test mode and wherein the receive circuit
further comprises a receive linear feedback logic gate, wherein a first receive shift
register output of the receive shift register is coupled to a first receive linear feedback
15 logic input of the receive linear feedback logic gate and wherein a second receive linear
feedback logic input of the receive linear feedback logic gate, the receive linear feedback
logic gate producing a receive linear feedback logic gate output signal upon which a
receive shift register input signal at a receive shift register input of the receive shift
register depends when the receive circuit is operating in the test mode.

5. The digital signaling system of claim 1 wherein the transmit repeating pattern
generator comprises a transmit linear feedback shift register and the receive repeating
pattern generator comprises a receive linear feedback shift register.

6. The digital signaling system of claim 1 wherein the transmit data output signal is
25 capable of representing two bits of information simultaneously over a single conductor.

7. The digital signaling system of claim 1 wherein the transmit data output signal is
communicated over a single conductor referenced to a ground voltage.

8. The digital signaling system of claim 1 wherein the transmit data output signal is communicated as a differential signal over two conductors.

9. A method for evaluating a digital signaling system comprising the steps of:
generating a transmit repeating pattern in a transmit circuit;
transmitting the transmit repeating pattern to a receive circuit;
generating a receive repeating pattern in the receive circuit; and
5 comparing the transmit repeating pattern to the receive repeating pattern to obtain
a comparison.

10. The method of claim 9 further comprising the steps of:
adjusting a parameter affecting operation of the transmit circuit based on the
10 comparison.

11. The method of claim 10 wherein the parameter is selected from a group consisting
of an output current, a crosstalk cancellation coefficient, and a self-equalization
coefficient.
15

12. The method of claim 9 wherein the step of generating a transmit repeating pattern
in a transmit circuit comprises the step of:
utilizing a shift register to generate the transmit repeating pattern.

13. The method of claim 12 wherein the step of utilizing a shift register to generate
the transmit repeating pattern comprises the step of:
utilizing a linear feedback shift register to generate the transmit repeating pattern.
20

14. The method of claim 9 wherein the step of transmitting the transmit repeating
25 pattern to the receive circuit further comprises the step of:
transmitting the transmit repeating pattern as a signal referenced to a ground.

15. The method of claim 9 wherein the step of transmitting the transmit repeating
pattern to the receive circuit further comprises the step of:
30 transmitting the transmit repeating pattern as a differential signal over a pair of
conductors.

16. The method of claim 9 wherein the step of transmitting the transmit repeating pattern to the receive circuit further comprises the step of:

transmitting the transmit repeating pattern by encoding two bits of information on
5 a single conductor simultaneously.

17. The method of claim 9 further comprising the step of:
adjusting a receiver characteristic of the receive circuit.

10 18. The method of claim 17 wherein the receiver characteristic is selected from a group consisting of an receive circuit timing signal and a voltage reference.

19. The method of claim 17 further comprising the step of:
determining boundary values of the receiver characteristic within which reliable
15 operation of the system is provided.

20. The method of claim 19 further comprising the steps of:
adjusting a parameter affecting operation of the transmit circuit based on the
boundary values.

20 21. The method of claim 20 wherein the parameter is selected from a group consisting of an output current, a crosstalk cancellation coefficient, and a self-equalization coefficient.